	REVISION DESCRIPTION	CHECK	APP	DATE	REV.NOTICE.NO
△1					
△2					
△3					







CONTAC TIP DETAIL



PERFORMANCE

1、Insulation Resistance: 1000MΩ Min.At DC 500V

2、Dielectric Withstanding Voltage For 1 Minute At AC 700V

3、Contact Resistance 30mΩ MAX。at 10mA and 20mV MAX.(Initial)

4、Current Rating: 1A max.

5、Operation Temperature -65°C ~+175°C

6、Life Span 25,000 Times (Mechanical)

7、Testing chips with balls of different size or superficial oxidation,even if no ball

PCB Pattern(TOP View)



Applicable IC



TOP VIEW



BOTTOM VIEW

SIDE VIEW

No	Part Number	Name	Material	Q/ty	Note
8	310-048-D105D	IC GUIDE	PEI/PES	2	BLACK
7	310-048-C105D	SLIDER	PEI/PES	1	BLACK
6	310-048-C105D	IC HOLDER	PEI/PES	2	BLACK
5	310-048-B105D	COVER	PEI/PES	1	BLACK
4	20-B-4505B	SPRING	SUS	4	FOR COVER
3	310-048-A105D	BASE	PEI/PES	1	BLACK
2	310-048-F105D	LOCATOR	PEI/PES	3	BLACK
1	04-A-1705	CONTACT	BeCu	100	Au PLATING

TOLERANCE	PROJECTION	GENERAL TOLERANCES	±0.10	TITLE	BGA100-1.0 SOCKET
		R E V	A	CLASS	BGA100-1.0-TP01NT
X. ±0.50	DIMENSION: mm	SCALE: 1:1		DRW.NO	007-BGA-1.0-100-12X18-B-01
X.X ±0.25	APP:	DATE:			
X.XX ±0.10	CHECK:	DATE:			
X.XXX ±0.05	DEGK: ENG03	DATE: 20160311			

HMILU